

By Order of the Maritime Administrator.  
**Joel C. Richard,**  
*Secretary, Maritime Administration.*  
 [FR Doc. 01-11267 Filed 5-3-01; 8:45 am]  
**BILLING CODE 4910-81-P**

**DEPARTMENT OF TRANSPORTATION**

**National Highway Traffic Safety Administration**

[Docket No. NHTSA-2001-9324]

**Highway Safety Programs; Conforming Products List of Screening Devices To Measure Alcohol in Bodily Fluids**

**AGENCY:** National Highway Traffic Safety Administration, DOT.

**ACTION:** Notice.

**SUMMARY:** This notice amends the Conforming Products List (CPL) of devices that conform to the Model Specifications for Screening Devices that Measure Alcohol in Bodily Fluids (59 FR 39382).

**EFFECTIVE DATE:** May 4, 2001.

**FOR FURTHER INFORMATION CONTACT:** Dr. James F. Frank, Office of Research and Traffic Records, Research and Evaluation Division (NTS-31), National Highway Traffic Safety Administration, 400 Seventh Street, SW., Washington, DC 20590; Telephone: (202) 366-5593.

**SUPPLEMENTARY INFORMATION:** On August 2, 1994, Model Specifications for Screening Devices to Measure Alcohol in Bodily Fluids were published in the **Federal Register** (59 FR 39382). In these model specifications, NHTSA recognized industry efforts to develop new technologies. These specifications established performance criteria and methods for testing alcohol screening devices using either breath or other bodily fluids to measure alcohol content. NHTSA established these specifications to support State laws that target youthful offenders (i.e., "zero tolerance" laws) and the Department of

Transportation's workplace alcohol testing program. NHTSA published its first CPL for screening devices on December 2, 1994 (59 FR 61923; with a correction in 59 FR 65128). Five devices were on that first list.

On August 15, 1995, NHTSA amended its CPL of screening devices to measure alcohol in bodily fluids in the **Federal Register** (60 FR 42214) by adding two additional devices to the list, thereby bringing the list to seven devices.

Since the publication of that list, five additional devices have been evaluated at the Volpe National Transportation Systems Center in Cambridge, MA and found to conform to the model specifications. Accordingly, these five devices, listed in alphabetical order, are being added to the CPL.

The first new listing is the "Alcohol  $\sqrt{TM}$ " disposable breath alcohol tubes manufactured by Akers Laboratories, Inc., of Thorofare, NJ. These are disposable tubes that use a potassium dichromate color change to indicate whether the BAC of a breath sample is above the 0.02 threshold. These devices passed all requirements of the model specifications except when read under sodium vapor lighting conditions. Hence, they are approved for use except under sodium vapor lighting conditions, and the manufacturer's package insert specifies this limitation.

The second new listing is the Alco Check 9000 manufactured by Alco Check International of Hudsonville, MI. This device differs from the Alco Check 3000 D.O.T. and the Alco Screen 3000 (the same device sold under two different names) in that it allows for the storage and retrieval of test data by use of an added memory chip. As the Alco Check 3000 D.O.T. and the Alco Screen 3000 already conform to these model specifications, and the added memory chip does not change the alcohol-measuring capability of the device, NHTSA did not require the new Alco

Check 9000 to be retested before listing it on this CPL for screening devices.

The third new device on the CPL is the ABI (Alcohol Breath Indicator) manufactured by HAN International Co. Ltd. of Seoul, Korea. This is an electronic device with a two-digit numerical display that uses a semiconductor sensor.

The last two devices are the "PAS IIIa" and the "PAS Vr" manufactured by PAS Systems International, Inc. of Fredericksburg, VA. These are both electronic devices that use a fuel cell sensor with a two-digit numerical display. The PAS IIIa and PAS Vr are modifications of two different passive alcohol sensors made by the same company, but with a disposable mouthpiece added so that an appropriate deep-lung air sample can be obtained for breath measurements.

Two housekeeping items are also addressed in this notice. First, the company previously listed as STC Diagnostics, Inc. has changed its name to OraSure Technologies, Inc. and the new CPL reflects the inclusion of the new company name in addition to the old one. The name of its product, the Q.E.D. A150 Saliva Alcohol Test, remains the same. Second, there are a number of handheld breath test devices on the NHTSA CPL for Evidential Breath Testers that frequently are used as screening devices. It should be noted that any device on the most recent NHTSA CPL for EBTs which was published on July 21, 2000 (65 FR 45419) that was tested against the 1993 Model Specifications for Evidential Breath Testers (58 FR 48705) also fully meets the requirements of the Model Specifications for Screening Devices that Measure Alcohol in Bodily Fluids. Both procedures evaluate the performance of instruments at the 0.020 BAC level.

The Conforming Products List is therefore amended as follows:

**CONFORMING PRODUCTS LIST OF ALCOHOL SCREENING DEVICES**

Manufacturer	Device(s)
Akers Laboratories, Inc., Thorofare, NJ .....	Alcohol $\sqrt{TM}$ 2
Alco Check International <sup>1</sup> , Hudsonville, MI .....	Alco Check 3000 D.O.T. Alco Screen 3000 Alco Check 9000
Chematics, Inc., North Webster, IN .....	ALCO-SCREEN 02 <sup>TM</sup> 3
Guth Laboratories, Inc., Harrisburg, PA .....	Alco Tector Mark X Mark X Alcohol Checker
Han International Co., Ltd., Seoul, Korea .....	A.B.I. (Alcohol Breath Indicator)
OraSure Technologies, Inc., Bethlehem, PA (Formerly STC Technologies, Inc.) .....	Q.E.D. A150 Saliva Alcohol Test
PAS Systems International, Inc., Fredericksburg, VA .....	PAS IIIa PAS Vr
Repco Marketing, Inc., Raleigh, NC .....	Alco Tec III
Roche Diagnostic Systems, Branchburg, NJ .....	On-Site Alcohol <sup>4</sup>
STC Technologies, Inc. ....	Q.E.D. A150 Saliva Alcohol Test

## CONFORMING PRODUCTS LIST OF ALCOHOL SCREENING DEVICES—Continued

Manufacturer	Device(s)
Sound Off, Inc. <sup>1</sup> , Hudsonville, MI .....	Digitox D.O.T. Alco Screen 1000

<sup>1</sup> The devices listed by these manufacturers are the same devices sold under different names.

<sup>2</sup> It should be noted that the Alcohol √ disposable breath alcohol screening device manufactured by Akers Laboratories, Inc. passed the model specifications under all lighting conditions except one, namely sodium vapor lighting. The device is being listed on this CPL with the understanding that the manufacturer will specify in written instructions accompanying the product that the device should not be used under sodium vapor lighting conditions. It passed the testing under all other conditions.

<sup>3</sup> While the ALCO-SCREEN 02™ saliva-alcohol screening device manufactured by Chematics, Inc. passed the requirements of the model specifications when tested at 40°C (104°F), the manufacturer has indicated that the device cannot exceed storage temperatures of 27°C (80°F). Instructions to this effect are stated on all packaging accompanying the device. Accordingly, the device should not be stored at temperatures above 27°C (80°F) and, if the device is stored at or below 27°C (80°F) and used at higher temperatures (i.e., within a minute), the devices met the model specifications and the results persisted for 10–15 minutes. When these devices were stored at or below 27°C (80°F) and were equilibrated at 40°C (104°F) for an hour prior to sample application, the devices failed to meet the model specifications. Storage at temperatures above 27°C (80°F), for even brief periods of time, may result in false negative readings.

<sup>4</sup> While this device passed all of the requirements of the model specifications, readings should be taken only after the time specified by the manufacturer. For valid readings, the user should follow the manufacturer's instructions. Readings should be taken one (1) minute after a sample is introduced at or above 30°C (86°F); readings should be taken after two (2) minutes at 18°C–29°C (64.4°–84.2°F); and readings should be taken after five (5) minutes when testing at temperatures at or below 17°C (62.6°F). If the reading is taken before five (5) minutes has elapsed under the cold conditions, the user is likely to obtain a reading that underestimates the actual saliva-alcohol level.

Note that the device made by Akers Laboratories, Inc. is a single-use, disposable breath test device. The devices manufactured by Chematics, Inc., OraSure Technologies, Inc., Roche Diagnostic Systems, Inc., and STC Technologies, Inc. are all single-use, disposable saliva alcohol test devices. The other devices listed are electronic breath testers. Those manufactured by PAS Systems International, Inc. use a fuel-cell sensor, whereas those manufactured by Alco Check International, Guth Laboratories, Han International Co., Ltd., Repco marketing, Inc., and Sound Off, Inc. use semiconductor sensors.

Issued on: May 1, 2001.

**Rose A. McMurray,**

*Associate Administrator for Traffic Safety Programs.*

[FR Doc. 01–11318 Filed 5–3–01; 8:45 am]

**BILLING CODE 4910–59–P**

## DEPARTMENT OF TRANSPORTATION

### National Highway Traffic Safety Administration

[Docket No. NHTSA–2001–9318]

RIN 2127–AG19

### Federal Motor Vehicle Safety Standards; Lamps, Reflective Devices, and Associated Equipment; Review: Effectiveness of Retroreflective Tape; Evaluation Report

**AGENCY:** National Highway Traffic Safety Administration (NHTSA), Department of Transportation.

**ACTION:** Request for comments on technical report.

**SUMMARY:** This notice announces NHTSA's publication of a Technical

Report reviewing and evaluating its existing Safety Standard 108, Lamps, Reflective Devices, and Associated Equipment. The report's title is The Effectiveness of Retroreflective Tape on Heavy Trailers.

**DATES:** Comments must be received no later than September 4, 2001.

**ADDRESSES:** *Report:* You may obtain a copy of the report free of charge by sending a self-addressed mailing label to Publications Ordering and Distribution Services (NAD–51), National Highway Traffic Safety Administration, 400 Seventh Street, SW., Washington, DC 20590. A summary of the report is available on the Internet for viewing on line at [www.nhtsa.dot.gov/cars/rules/regrev/evaluate/809222.html](http://www.nhtsa.dot.gov/cars/rules/regrev/evaluate/809222.html). The full report is available on the Internet in PDF format at [www.nhtsa.dot.gov/cars/rules/regrev/evaluate/pdf/809222.pdf](http://www.nhtsa.dot.gov/cars/rules/regrev/evaluate/pdf/809222.pdf).

*Comments:* All comments should refer to the Docket number of this notice (NHTSA–2001–9318). You may submit your comments in writing to: U. S. Department of Transportation Docket Management, Room PL–401, 400 Seventh Street, SW., Washington, DC 20590. You may also submit your comments electronically by logging onto the Dockets Management System website at <http://dms.dot.gov>. Click on “Help & Information” or “Help/Info” to obtain instructions for filing the document electronically.

You may call Docket Management at 202–366–9324 and visit the Docket from 10:00 a.m. to 5:00 p.m., Monday through Friday.

**FOR FURTHER INFORMATION CONTACT:** Charles J. Kahane, Chief, Evaluation Division, NPP–22, Plans and Policy, National Highway Traffic Safety Administration, Room 5208, 400 Seventh Street, SW, Washington, DC

20590. Telephone: 202–366–2560. FAX: 202–366–2559. E-mail: [ckahane@nhtsa.dot.gov](mailto:ckahane@nhtsa.dot.gov).

*For information about NHTSA's evaluations of the effectiveness of existing regulations and programs:* Visit the NHTSA web site at <http://www.nhtsa.dot.gov> and click “Regulations & Standards” underneath “Car Safety” on the home page; then click “Regulatory Evaluation” on the “Regulations & Standards” page.

**SUPPLEMENTARY INFORMATION:** The technical report evaluates the effectiveness of retroreflective tape in enhancing the visibility of heavy trailers and reducing side and rear impacts by other vehicles into these trailers during dark conditions. It is based on a statistical analysis of 10,959 crash cases investigated by the Florida Highway Patrol and the Pennsylvania State Police in 1997–1999.

The tape is quite effective. It reduced side and rear impacts into trailers, in dark conditions (including “dark-not-lighted,” “dark-lighted,” “dawn,” and “dusk”) by 29 percent. In “dark-not-lighted” conditions, the tape reduced side and rear impact crashes by 41 percent. Tape is especially effective in reducing injury crashes. In dark conditions, it reduced side and rear impacts that resulted in fatalities or injuries to drivers of any vehicle by 44 percent.

### How Can I Influence NHTSA's Thinking on This Evaluation?

NHTSA welcomes public review of the technical report and invites reviewers to submit comments about the data and the statistical methods used in the analyses. NHTSA will submit to the Docket a response to the comments and, if appropriate, additional analyses that

supplement or revise the technical report.

### How Do I Prepare and Submit Comments?

Your comments must be written and in English. To ensure that your comments are correctly filed in the Docket, please include the Docket number of this document (NHTSA–2001–9318) in your comments.

Your primary comments must not be more than 15 pages long (49 CFR 553.21). However, you may attach additional documents to your primary comments. There is no limit on the length of the attachments.

Please send two paper copies of your comments to Docket Management or submit them electronically. The mailing address is U.S. Department of Transportation Docket Management, Room PL–401, 400 Seventh Street, SW., Washington, DC 20590. If you submit your comments electronically, log onto the Dockets Management System website at <http://dms.dot.gov> and click on “Help & Information” or “Help/Info” to obtain instructions.

We also request, but do not require you to send a copy to Christina Morgan, Evaluation Division, NPP–22, National Highway Traffic Safety Administration, Room 5208, 400 Seventh Street, SW., Washington, DC 20590 (alternatively, FAX to 202–366–2559 or e-mail to [tmorgan@nhtsa.dot.gov](mailto:tmorgan@nhtsa.dot.gov)). She can check if your comments have been received at the Docket and she can expedite their review by NHTSA.

### How Can I Be Sure That My Comments Were Received?

If you wish Docket Management to notify you upon its receipt of your comments, enclose a self-addressed, stamped postcard in the envelope containing your comments. Upon receiving your comments, Docket Management will return the postcard by mail.

### How Do I Submit Confidential Business Information?

If you wish to submit any information under a claim of confidentiality, send three copies of your complete submission, including the information you claim to be confidential business information, to the Chief Counsel, NCC–01, National Highway Traffic Safety Administration, Room 5219, 400 Seventh Street, SW., Washington, DC 20590. Include a cover letter supplying the information specified in our confidential business information regulation (49 CFR part 512).

In addition, send two copies from which you have deleted the claimed confidential business information to Docket Management, Room PL–401, 400 Seventh Street, SW, Washington, DC 20590, or submit them electronically.

### Will the Agency Consider Late Comments?

In our response, we will consider all comments that Docket Management receives before the close of business on the comment closing date indicated above under DATES. To the extent possible, we will also consider comments that Docket Management receives after that date.

Please note that even after the comment closing date, we will continue to file relevant information in the Docket as it becomes available. Further, some people may submit late comments. Accordingly, we recommend that you periodically check the Docket for new material.

### How Can I Read the Comments Submitted by Other People?

You may read the comments by visiting Docket Management in person at Room PL–401, 400 Seventh Street, SW., Washington, DC from 10:00 a.m. to 5:00 p.m., Monday through Friday.

You may also see the comments on the Internet by taking the following steps:

- a. Go to the Docket Management System (DMS) Web page of the Department of Transportation (<http://dms.dot.gov>).

- b. On that page, click on “search.”

- c. On the next page (<http://dms.dot.gov/search/>) type in the four-digit Docket number shown at the beginning of this Notice (6545). Click on “search.”

- d. On the next page, which contains Docket summary information for the Docket you selected, click on the desired comments. You may also download the comments.

**AUTHORITY:** 49 U.S.C. 30111, 30168; delegation of authority at 49 CFR 1.50 and 501.8.

**William H. Walsh,**

*Associate Administrator for Plans and Policy.*  
[FR Doc. 01–11163 Filed 5–3–01; 8:45 am]

**BILLING CODE 4910–59–P**